

KCIB602VSN

Long Range HR Infrared Varifocal Camera

Features

- 700 Lines Resolution
- 200 ft. IR View Distance
- 5~50mm Varifocal Lens
- ICR (True Day / Night)
- IR LED Controls
- Cable Management Bracket
- Vandal Resistant
- Weatherproof
- External Zoom / Focal Adjustment
- Installer Video Out
- Dual Voltage (DC12V/AC24V)



Model	KCIB602VSN
Image Sensor	1/3" Sony Super HAD II CCD
Lens Type	5-50mm Varifocal Lens (DC Auto Iris)
Mount	Wall or Ceiling
Effective Pixels (HxV)	768 x 494
Total Pixels (HxV)	811 x 508
Resolution	700 TV Lines
S/N Ratio	> 52db (AGC Off)
Min. Illumination	0.1 Lux / 0 Lux (IR On)
Infrared	200 ft (12 Hi-Power LEDs & 24 LEDs)
Auto Gain Control	Off / Low / Middle / High
White Balance	ATC / Manual / Push
Electronic Shutter	1/60s - 1/100,000s (NTSC)
3D-DNR (Digital Noise Reduction)	On / Off Selectable (Low / Middle / High)
Sens-Up	Off / Auto (x2-x1024)
Back Light Compensation	On / Off Selectable
D&N Selection	Auto / Color / BW / EXT
D-WDR	On / Off Selectable
Dead Pixel	Off / Auto (Max 64 pts)
Motion Detection	On / Off (1-4 areas selectable)
Mirror	On / Off Selectable
HLM	On / Off Selectable
IR Smart	On / Off Selectable
Privacy Masking	On / Off (1-8 areas selectable)
Sharpness	On / Off Selectable (level adjustable 1-50)
Weatherproof Rating	IP66
OSD	Built In
Power (Supply Not Included)	DC 12V / AC24V, 150mA (CDS ON: 600mA Max)
Working Environment	14°F to 122°F (-10°C to 50°C) / 0 ~ 80% Humidity
Dimensions (HxWxD) / Weight	3.5" x 3.4" x 7" (88mm x 87mm x 177mm) / Appx. 2.65 lbs (1200g)
Warranty	1 Year