


HDCB4M-28

4.0 Megapixel 2.8mm Fixed 1080P HD-over-Coax Bullet



Features

- 1/3" CMOS
- 30fps @ 4MP / 1080P / 720P
- High speed, long distance real-time transmission
- OSD Menu, Control over Coaxial Cable
- Day/Night (ICR), AWB, AGC, BLC, 2D-DNR
- 2.8mm fixed lens
- Max. IR LEDs length 98ft , Smart IR
- IP67, DC12V



Specifications

| HDCB4M-28 | | |
|---------------------------------|---|-------------|
| Image Sensor | 1/3" CMOS | |
| Resolution | HD-over-Coax | 2688 x 1520 |
| | Analog | 700 TVL |
| Frame Rate | 30fps @ 4MP; 25/30fps @ 1080P; 25/30fps @ 720P | |
| Electronic Shutter | 1/3 ~ 1/100,000s | |
| Effective Picture (H × V) | 2688 x 1520 | |
| Video Output | 1 × BNC - HD (can switch to CVBS) | |
| Focal Length | 2.8mm | |
| Lens Type | Fixed | |
| Min. Illumination Color / B&W | 0.03 Lux @ F2.0 (0 Lux IR LED on) | |
| Infrared Range | 98ft. (Max.) | |
| Day / Night | Auto (ICR) / B&W / Color | |
| Noise Reduction | 2D | |
| OSD Menu | Supported | |
| Angle of View | H: 99.7° | |
| Close Focus Distance | 31.5" | |
| DORI | Detect | 208ft |
| | Observe | 83ft |
| | Recognize | 42ft |
| | Identify | 21ft |
| WDR Type | Digital Wide Dynamic Range | |
| Weatherproof Rating | IP67 | |
| Transmission Distance | Over 1,640ft (500m) via 75-3 coaxial cable | |
| Bracket Included | No | |
| Power Supply / Consumption | 12V±10% DC / 4.6W | |
| Working Environment | -40°F ~ 140°F, less than 95% RH (no condensation) | |
| Dimensions / Weight | 6.48"×2.76"×2.82" / Approx. 1 lbs | |