


HDCD4M-28W / HDCD4M-28L

4.0 Megapixel 2.8mm Fixed 1080P HD-over-Coax Armor Ball



Features

- 1/3" CMOS
- 30fps @ 4MP / 1080P / 720P
- High speed, long distance real-time transmission
- OSD Menu, Control over Coaxial Cable
- Day/Night (ICR), AWB, AGC, BLC, 2D-DNR
- 2.8mm fixed lens
- Max. IR LEDs length 98ft , Smart IR
- IP67, DC12V



Specifications

		HDCD4M-28L	HDCD4M-28W
Image Sensor		1/3" CMOS	
Resolution	HD-over-Coax	2688 x 1520	
	Analog	700 TVL	
Frame Rate		30fps @ 4MP; 25/30fps @ 1080P; 25/30fps @ 720P	
Electronic Shutter		1/3 ~ 1/100,000s	1/3 ~ 1/300,000s
Effective Picture (H × V)		2688 x 1520	
Video Output		1 × BNC - HD (can switch to CVBS)	
Focal Length		2.8mm	
Lens Type		Fixed	
Min. Illumination Color / B&W		0.03 Lux @ F2.0 (0 Lux IR LED on)	0.03 Lux @ F1.5 (0 Lux IR LED on)
Infrared Range		98ft. (Max.)	
Day / Night		Auto (ICR) / B&W / Color	
Noise Reduction		2D	3D
OSD Menu		Supported	
Angle of View			
Close Focus Distance			
DORI	Detect	208ft	
	Observe	83ft	
	Recognize	42ft	
	Identify	21ft	
WDR Type		Digital Wide Dynamic Range	True Wide Dynamic Range
Weatherproof Rating		IP67	
Transmission Distance		Over 1,640ft (500m) via 75-3 coaxial cable	
Bracket Included		No	
Power Supply / Consumption		12V±10% DC / 3.2W	12V±10% DC / 4.8W
Working Environment		-22°F ~ 140°F (-30°C ~ 60°C), less than 80% RH (no condensation)	
Dimensions / Weight		3.7" x 3.2" / Approx. 0.7 lbs	