


HDCD4M-36

4.0 Megapixel 1080P HD-over-Coax Camera



Features

- 1/3" CMOS
- 25fps @ 4MP, 25/30fps @ 1080P, 25/30fps @ 720P
- High speed, long distance real-time transmission
- Analog / HD Switchable via BNC Connections
- OSD Menu, Control over Coaxial Cable
- Day/Night (ICR), AWB, AGC, BLC, 3D-DNR
- 3.6mm fixed lens
- Max. IR LEDs length 98ft (30m), Smart IR
- IP67, DC12V



Specifications

		HDCD4M-36
Image Sensor		1/3" CMOS
Resolution	HD-over-Coax	2688 x 1520
	Analog	700 TVL
Frame Rate		25fps @ 4MP; 25/30fps @ 1080P; 25/30fps @ 720P
Electronic Shutter		1/3 ~ 1/300,000s
Effective Picture (H × V)		2688 x 1520
Video Output		1 × BNC - HD / 1 x BNC - Analog
Focal Length		3.6mm
Lens Type		Fixed
Min. Illumination Color / B&W		0.03 Lux @ F1.5 (0 Lux IR LED on)
Infrared Range		98ft. (Max.)
Day / Night		Auto (ICR) / B&W / Color
Noise Reduction		2D / 3D
Weatherproof Rating		IP67
Transmission Distance		Over 1,640ft (500m) via 75-3 coaxial cable
Bracket Included		No
Power Supply		12V±10% DC
Working Environment		-22°F ~ 140°F (-30°C ~ 60°C), less than 80% RH (no condensation)
Dimensions / Weight		3.7" x 3.2" / Approx. 0.7 lbs