

# Optiview VMS

Video Management System



## Features

- Support IP/Megapixel, HD-over-Coax, DVR, NVR, etc.
- Live Preview supports up to 64 (x) 4 Preview Windows; Main/Sub-stream optional
- Auto find/import/export supported
- Manage up to 256 devices (up to 2048 channels)
- 36 channel playback / 64 channel live view / 16 channel record
- On-screen Joystick to control PTZ
- Zoom in/out + Fish-eye camera EPTZ using mouse
- Center alarm for organizing alarm channels
- Support e-map; clearly view & manage all device locations
- Account management supported; different users share different privileges
- Activity Log for event & user operation
- Graphical User Interface for easy operation

## Specifications

Model	
Supported Devices	IP / Megapixel, HD-over-Coax, DVR, NVR
Max Registered Devices	256 Individual IP Cameras or Video Recorders (up to 2048 channels)
Device Management	Auto find, Add, Delete, Device Group, Reboot, Set-Up
Health Report	Device Status, Alarm Info, HDD Info
Video Display Split	1 / 4 / 6 / 8 / 9 / 16 / 25 / 36 or customize split for all versions. 64 way split only available for Windows.
Multiple Screen View	4 x 64 Channel Windows   1 x 36 Channel Window
Features	Snapshot, Record, Audio, Talk, Instant Replay, E-PTZ, Tour Task
PTZ Control	Directions, PTZ, Focus, Iris, Preset, Tour, Pattern, Joystick Control
Alarm Output Control	Support
Video Source	Local PC (Manual record or alarm record), Embedded DVR/NVR, IP/Megapixel, HD-over-Coax
Playback	Up to 24 hours at a time / Up to 36 Channels at a time
Search Type	Certain time, motion detection, alarm
Features	Snapshot, E-PTZ, Audio, Speed 1/8x~8x, Synchronization Playback
Video Back-Up	Export as: .dav or .avi   Export as: .dav
Alarm Features	Schedule alarms, set up actions, operate / memo alarm
Alarm Type	External alarm, video loss, motion, tampering, disk full or error
Alarm Actions	Trigger recording, PTZ movement, alarm, popup video
Number of E-Maps	Map group: Unlimited, Sub-Map, Layout: 64
E-Map Supports Image Types	JPEG / BMP
Local Recording	Record up to 16 channels locally
Device Configuration	Network, encode, PTZ, image, event, record, disk, account, maintenance
Account	User & Role management; privileges according to module & device
Log	Client log, remote device log; operation log, system log, alarm log
System Requirement	CPU: 2 Cores, 3.0GHZ or above Memory: 2G or above; HDD 80G or above
Operating System	Windows XP / Vista / 7 / 8 / 10 OS 10.7 or above