

TESTMON-DQ

Portable IP Camera Tester



Overview

The 4 inch IPS touch screen IP camera tester is designed for maintenance and installation of IP analog, HD coaxial cameras as well as other security equipment. The 800*480 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. CCTV installers often need to carry a variety of testing tools to complete their work. If take the all in one camera tester, making working conditions safer and increasing productivity.

Features

- 8MP TVI/4MP CVI/5MP AHD/CVBS/4K H.265 IP
- H.265/H.264, 4K video display via mainstream
- 3.DC12V 3A, DC48V PoE power output.
- Rapid ONVIF, auto view video and create testing report
- 10/100/1000M Ethernet, network state and traffic display.
- Wrist design, portable and easier to carry.

Specifications

Model	TESTMON-DQ
Display	4in IPS touch screen
Power Output	48V PoE power output, max power 24W
Network Test	Link monitor, port flashing, ping test
Audio Test	1 channel audio signal input
Data Monitor	Captures and analyzes the command data from controlling device
Drop-down Menu	Can select PoE power switch, IP setting, CVBS, LAN info, etc in any interface
External Power Supply	DC 12V 1A
Battery	Built-in 7.4V Lithium polymer battery, 2400mAh
Rechargeable	Full charge in 5 hours.
Operation Setting	OSD menu with language select
Support Languages	English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese
Auto Off	1-30 (mins)
Working Temperature	-10°C - 50°C; <90% Humidity
Dimension	126mm x 83mm x 33mm
Weight	0.32kg
CVBS	1 channel BNC input (NTSC/PAL), PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols
IP Camera Test (4K/H.265/H.264)	IP Discovery/Quick ONVIF/IPC Test/RTSP Play/Client APK
Coaxial HD Test	8mp TVI camera test, 4mp CVI camera test, and 5mp AHD test
Zoom Image	4x
12V/3A Power	Output DC12V/3A power out