

LPRIP2M-550

2 Megapixel Full HD WDR Access LPR Camera



Features

- Embedded with LPR algorithm inside the camera
- Support plate cutout, overview picture snapshot and video recording
- Embedded with White list database, control the barrier
- Powerful 5-50mm manual lens and white light, ideal for monitor ANPR distance as 40m
- Wide working temperature, IP66 and superior performance for outdoor applications
- True WDR technology



Model	LPRIP2M-550
Image Sensor	1/2.8 inch 2 Megara CMOS
Scanning System	Progressive
Min Illumination	0.002Lux/F1.2 Color 0Lux/F1.2IR on
Electronic Shutter Speed	1/50 ~ 1/10,000
Lens Type / Mount	Manual / C
Max Aperture	F1.6
Angle of View	H: 50° ~ 5.6° V: 37.5° ~ 4.2°
Effective Picture (H×V)	1920 x 1080
Video Frame Rate	1080P @ 30fps
Video Output	1080P - CVI / TVI / AHD / Analog
Compression	H.265 / H.264M / H.264H / H.264B
White Light Distance	131ft (40m)
White LEDs	6
OSD Menu	Supported
Transmission Distance	Over 1100ft (350m) via 75-3 coaxial cable
Edge Storage	Micro SD (Max 64GB)
Waterproof Rating	IP66
Power (Supply / Consumption)	POE+ / 17W
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C) / Less than 95% RH (no condensation)
Dimensions	17.6" x 9.5" x 9.2" (447mm x 240mm x 233mm)
Weight	9 lbs (4.1kg)
Warranty	1 Year