

TESTMON-4-DMM

Portable Anallon / CVI / TVI / AHD Camera Tester



Overview

All new 4-in-1 (Analog / CVI / TVI / AHD) test monitor with 4" screen, and digital multi-meter. The TESTMON-4-DMM supports up to 4K CVI and TVI, as well as 5MP AHD resolutions. Also supports testing audio functionality.

Features

- 4.0" LCD Touch Screen (800 x 480)
- Test Analog, HD-over-Coax and IP Cameras
- PoE 24W Power Supply to IP Cameras
- DC12V 2A Power Output for Cameras
- TDR Testing
- Audio input testing

Specifications

| Model | TESTMON-4-DMM |
|---------------------|---|
| Display | 4.0 inch LCD display with touch screen |
| Video Format | NTSC, PAL auto recognize / HD CVI, AHD, HD TVI auto recognize |
| Power Output | 12V 1A DC |
| Network Test | N/A |
| Audio Test | 1 channel Audio input 1 channel Audio output (connect to headphones) |
| Battery | 1 pcs Lithium Ion Polymer Battery; 7.4V DC, 5000mAh |
| Rechargeable | 2 hours charge, works for 5 hours |
| Operation Setting | OSD menu with language select |
| Baud Rate | 150bps, 300bps, 600bps, 1200bps, 2400bps, 4800bps, 9600bps, 19200bps |
| Support Languages | English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese, German, Turkish, Czech, Portuguese, Romanian, Serbian, Finnish, Arabic |
| CVBS | 1 channel BNC input (NTSC/PAL), PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols |
| Button Functions | Focus, Zoom, and Iris controls |
| Working Temperature | 14°F - 131°F (-10°C - 55°C) @ 30-90% Humidity |
| Dimension | 6.9" x 4.5" x 1.5" (175mm x 113mm x 37mm) |
| Weight | 3.9 pounds (1780g) |