

# TESTMON-5-DMM

Portable Anallon / CVI / TVI / AHD Camera Tester



## Overview

All new 5-in-1 (Analog / CVI / TVI / AHD / IP) test monitor with 4" screen, flip out QWERTY keyboard, and digital multi-meter. The TESTMON-5-DMM supports up to 4K IP, CVI and TVI, as well as 5MP AHD resolutions. Also supports testing audio functionality.

## Features

- 4.0" LCD Touch Screen (800 x 480)
- Dual 1Gbps Ethernet Ports
- Test Analog, HD-over-Coax and IP Cameras
- PoE 24W Power Supply to IP Cameras
- DC12V 2A Power Output for Cameras
- TDR Testing
- Audio input testing

## Specifications

Model	TESTMON-5-DMM
Display	4.0 inch LCD display with touch screen
Video Format	NTSC, PAL auto recognize / HD CVI, AHD, HD TVI auto recognize
Power Output	12V 1A DC
Network Test	ONVIF, RTSP, RTP Supported
IPC Test	Discover camera, real time video, camera configuration, PTZ Control, discover ONVIF devices across network segments
Audio Test	1 channel Audio input 1 channel Audio output (connect to headphones)
Battery	7.4V lithium-ion Polymer Battery, Capacity 22.2Wh
Rechargeable	3.5 hours charge, works for 10 hours
Operation Setting	OSD menu with language select
Baud Rate	150bps, 300bps, 600bps, 1200bps, 2400bps, 4800bps, 9600bps, 19200bps
Support Languages	English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese, German, Turkish, Czech, Portuguese, Romanian, Serbian, Finnish, Arabic
CVBS	1 channel BNC input (NTSC/PAL), PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols
Button Functions	PTZ Focus, Zoom, and Iris.
Working Temperature	14°F - 131°F (-10°C - 55°C) @ 30-90% Humidity
Dimension	7.5" x 4.5" x 1.5" (190mm x 113mm x 37mm)
Weight	3.9 pounds (1780g)